

## POLYCORP C-100

### Chemlok 205

May 2014

**Polycorp C-100/Chemlok 205** is a primer designed for use under Chemlok cover-coat adhesives to bond a wide variety rubber lining to metal. It provides excellent environmental resistance and is suitable for use with autoclave, open steam and chemical cures.

#### TYPICAL PROPERTIES:

	<b>CHEMLOK 205/C-100 PRIMER</b>
Composition	A mixture of polymers, organic compounds and fillers dissolved in an organic solvent system.
Color	Gray Liquid
% NV by weight	22.0 – 26.0%
Viscosity, cps @ 77° F (25°C) Brookfield LVT Spindle 2, 30 rpm	85 - 165
Weight/ Gal.	7.6 – 8.1 lb/gal
Solvents	MIBK, MEK, Xylene
Theoretical Coverage	300 sq. ft./gal
Shelf Life	One year from date of shipment, unopened container stored @ 70°F- 80°F (21°C- 26°C)

\*Typical properties based on technical data sheet from Lord. Product information available @ [www.lord.com](http://www.lord.com)

#### Application:

C-90 / Chemlok 205 can be applied using a roller or brush. Thoroughly stir Primer before use. During use agitate sufficiently to keep dispersed solids uniformly suspended. Please refer to section 8 of Application Manual for general application instructions. Complete product information also available @ [www.lord.com](http://www.lord.com)

#### Safety:

Before using this product please refer to the Material Safety Data Sheet (MSDS) for safe use and handling.